

# **PRODUCT DATASHEET**

Magnetic Track Light HD750-24W 4000K



# Application

- Hotel
- Mall
- Supermarket
- Theater
- Shop

## **Benefits**

- Flicker free
- Adjustable Angle, flexible light control
- Minimum Glare, more clear and comfortable
- High color rendering index, restore the true color of the object, show its beauty

### Features

- Warranty 3 years
- High efficiency lens design, resulting in a clear edge of the soft spot
- Die-cast aluminum lamp body, good heat dissipation performance, protect the chip, extend the service life

January,25,2024 Product Datasheet HD750-24W 4000K





#### **Electrical Data**

| Nominal wattage (W)  | 24W                   |  |
|----------------------|-----------------------|--|
| Nominal Voltage (V)  | 48V                   |  |
| Mains Frequency (Hz) | 60                    |  |
| Nominal Current (mA) | 494                   |  |
| Power Factor         | 1                     |  |
| Operating mode       | Magnetic Track Driver |  |

#### **Photometrical data**

| Luminous flux ±10% (lm)              | 2216 lm       |  |  |
|--------------------------------------|---------------|--|--|
| Luminous efficacy                    | 94 lm/w       |  |  |
| Color temperature                    | 4000K         |  |  |
| Light color (designation)            | Natural White |  |  |
| Color rendering index Ra             | ≥90           |  |  |
| Standard deviation of color matching | ≤5 SDCM       |  |  |
| Luminous intensity/cd                | 14706         |  |  |
| Flickering                           | Flicker free  |  |  |
| Beam angle                           | 21 °          |  |  |






# **4000K**



# **Dimensions & Weight**

| Diameter (mm)      | 75  |
|--------------------|-----|
| Height (mm)        | 165 |
| Product weight (g) |     |



D 75 mm

#### Material & Colors

| Product color   | Black    |  |  |
|-----------------|----------|--|--|
| Housing color   | Black    |  |  |
| Body material   | Aluminum |  |  |
| Cover material  | PC       |  |  |
| Mercury content | 0.0 mg   |  |  |

# **Application & Mounting**

| Ambient temperature range    | -20°C~+45 °C           |  |  |
|------------------------------|------------------------|--|--|
| Temperature range at storage | -20°C~+60 °C           |  |  |
| Type of connection           | Screwless terminal     |  |  |
| Type of protection           | IP20                   |  |  |
| Dimmable                     | No                     |  |  |
| Mounting type                | Magnetic Track Mounted |  |  |
| Mounting location            | Ceiling / Wall         |  |  |
| Application environment      | Indoor                 |  |  |
| Cut size (mm)                | No                     |  |  |
| LED module replaceable       | Not replaceable        |  |  |
| With light source            | Yes                    |  |  |
|                              |                        |  |  |




#### **Certificates & Lifespan**

| Life (h)     | 30,000          |
|--------------|-----------------|
| Certificates | CB LVD EMC RoHS |
| Standards    | ISO9001:2015    |

## Logistical Data

| Product code | Dimensions  | Pcs/   | G.W. | Volume |
|--------------|-------------|--------|------|--------|
|              | (L*W*H)     | carton | kg   | CBM    |
| HD750-24W    | 53*42*46 cm | 30     | •••  | 0.1024 |

## **Installation Method**



### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.