

#### PRODUCT DATASHEET

### LAWN LIGHT HYD-L01-C-10W 3000K



# **Application**

- Courtyard
- Plaza
- Park
- Pedestrian street
- Meadow

#### **Benefits**

- energy saving and environmental protection
- Low power, high light efficiency
- IP65 is water and dust resistant to harsh environment
- Lawn lights decorate the outdoor space to enhance high outdoor comfort

#### **Features**

- Seiko aluminum, rust and corrosion resistant
- The lighting facilities around the lawn are important landscape facilities, and the installation method is also simple
- High light transmission mask ensures uniform light and reduces the lighting environment in dark areas





## **Electrical Data**

Nominal wattage (W)	10W
Nominal Voltage (V)	220-240V
Mains Frequency (Hz)	50
Nominal Current (mA)	78
LED Driver Current (mA)	250
LED Driver Voltage (VDC)	28-42
LED Driver Efficiency (%)	≥83%
Power Factor λ	0.55
Total harmonic distortion (%)	
Operating mode	Built in

### **Photometrical data**

Luminous flux ±10% (lm)	466 lm		
Luminous efficacy	47 lm/w		
Color temperature	3000K		
Light color (designation)	Warm White		
Color rendering index Ra	≥80		
Standard deviation of color matching	≤5 SDCM		
Luminous intensity/cd	3668		
Flickering	Flicker free		
Beam angle	18 °		






**IES** 



**Dimensions & Weight** 

Diameter (mm)/A&B	64*138
Height (mm)/C	310
Product weight (g)	



# **Material & Colors**

Product color	Black	
Housing color	Black	
Body material	Aluminum	
Cover material	Glass	
Mercury content	0.0 mg	

**Application & Mounting** 

Ambient temperature range	-10°C~+40 °C	
Temperature range at storage	-10°C~+40 °C	
Type of connection	Screw terminal	
Type of protection	IP65	
Dimmable	No	
Mounting type	Recessed	
Mounting location	underground	
Application environment	Outdoor	
Cut size (mm)	No	
LED module replaceable	Not replaceable	
With light source	Yes	




**Certificates & Lifespan** 

Life (h)	30,000		
Certificates	CB LVD EMC RoHS		
Standards	ISO9001:2015		

# **Logistical Data**

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-L01-C-10W	48*48*24	20	•••	0.05530

# **Installation Method**



# **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release