

PRODUCT DATASHEET

RECESSED PANEL LIGHT HYD-104B-40W



Application

- Office
- Kitchen
- Rest room
- Corridor
- Shop

Benefits

- · Flicker free.
- The light is soft and bright
- Drive stable, safe and reliable
- High light transmission mask to ensure uniform light

Features

- Efficient and durable
- Easy and quick installation
- Light body thin design, reduce space occupancy
- Die-cast aluminum body for better heat dissipation, anti-corrosion, and easy maintain





Electrical Data

Nominal wattage (W)	40W	
Nominal Voltage (V)	220-240V~	
Mains Frequency (Hz)	50/60	
Nominal Current (mA)	179	
LED Driver Current (mA)	900	
LED Driver Voltage (VDC)	24-42	
LED Driver Efficiency (%)	89%	
Power Factor λ	0.9	
Total harmonic distortion (%)	<10%	
Operating mode	External LED driver	

Photometrical data

Luminous flux ±10% (lm)	4529 lm	
Luminous efficacy	111 lm/w	
Color temperature	3K/4K/ 6K	
Light color (designation)	Cold White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤5 SDCM	
Luminous intensity/cd	1580	
Flickering	Flicker free	
Beam angle	114 °	








Dimensions & Weight

Diameter (mm)	595*595
Height (mm)	32
Product weight (g)	



Material & Colors

Product color	All White		
Housing color	White		
Body material	Iron		
Cover material	PS diffuser material and PMMA lens		
Mercury content	0.0 mg		

Application & Mounting

Ambient temperature range	-10°C~+40 °C		
Temperature range at storage	-10°C~+40 °C		
Type of connection	Screwless terminal		
Type of protection	IP20		
Dimmable	No		
Mounting type	Recessed mounted		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	/		
LED module replaceable	Not replaceable		
With light source	Yes		

Certificates & Lifespan


Life (h)	30,000	
Certificates	CB LVD EMC RoHS	
Standards	ISO9001:2015	



Logistical Data

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-104B-40W	64.5*22*63 cm	5	•••	0.08940

Installation Method



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release